

# X-Road Team Issue Di2 GR

MATTE BLACK/OLIVE METALLIC



GRAPHIC SIMULATION ONLY / REAL PICTURE SOON

ROAD & GRAVEL / GRAVEL

## BENEFITS

- Internal Cable Routing for perfect integration: clean, modern looks without outside tubing or cabling
- Carbon handlebar&stem cockpit combo
- Concealed mounting points to fit mudguards
- Schwalbe G-One tires: fast on tarmac, safe on gravel roads
- Wide gear range: 1x11 with 11-42t cassette

## GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	462	482	502	522
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	531	544	568	590
REACH (MM)	376	379	392	408
STACK HEIGHT (MM)	536	557	578	597
HEAD TUBE LENGTH (MM)	120	140	160	180
HEAD TUBE ANGLE (DEGREE)	71	71.5	72	72
CHAINSTAY LENGTH (MM)	412	412	412	412
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	990	996	1010	1032
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	380	380	380	380

## SPECIFICATION

### FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB865, SH dropout, Thru Axle 12x142 mm, Inner cable routing, Di2 compatible, mudguards ready
HEAD SET	ACROS AIX-525, OD56, IS52/28.6, ICR-IS52/40IPS
FORK	X-ROAD carbon fork
COLOUR	MATTE BLACK/OLIVE METALLIC
SIZES	52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

### DRIVETRAIN

REAR DERAILLEUR	SHIMANO GRX RD-RX817 Di2 Shadow Plus
CRANKSET	SHIMANO GRX FC-RX810 Hollowtech II, 42T
CASSETE	SHIMANO CS-M7000-11, 11-42T

<b>BOTTOM BRACKET</b>	SHIMANO BB-RS500 PressFit, shell 41x86.5mm, BB accessories
<b>CHAIN</b>	KMC X11
<b>COMPONENTS</b>	
<b>HANDLEBAR</b>	Handle bar
<b>GRIPS</b>	Velo VLF-8111
<b>BRAKES</b>	SHIMANO ST-RX815/BR-RX810, hydraulic disc brake
<b>SADDLE</b>	Fizik Terra Argo X5
<b>SEAT POST</b>	ONE1 Carbon, SP0225380AERO
<b>WHEELS</b>	
<b>TIRES</b>	Schwalbe G-One Allround RaceGuard, 28x1.50"
<b>WHEELSET</b>	DT Swiss GR 1600 Spline DB25; 12x142mm, CENTER LOCK, Tubeless, DT Swiss GR 1600 Spline DB25; 12x100mm, CENTER LOCK, Tubeless