

XF 999 TR

MATTE BLACK/OLIVE METALLIC



MTB FULL-SUSPENSION / TRAIL

BENEFITS

- New kinematics, 130 mm travel, and responsive Rock Shox suspension
- Integrated down tube and chainstay protectors
- Block Lock headset: frame protected against damage by handlebars
- Dropper post for better control in rough terrain, 4-piston brakes
- The frame allows attaching two bottle cages
- Schwalbe Nobby Nic 2,35" tubeless-ready tires: a superior grip and few flats
- DT Swiss M1900 SPLINE wheelset with a 30 mm rim for a better tire fit and traction

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	407	429	449	465
STACK HEIGHT (MM)	589	600	608	617
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	29	29	29	29
WHEELBASE (MM)	1154	1180	1200	1220
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	70	70	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 130 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°, Head set cover
FORK	RockShox Revelation RC, Tapered, DebonAir, 15x110mm axle, 140mm travel
REAR SHOCK	Bushing body for RockShox, RockShox Monarch RT, size 190x51mm
COLOUR	MATTE BLACK/OLIVE METALLIC
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE XT SL-M8100 RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8120 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M8100-12, 10-51T
BOTTOM BRACKET	SHIMANO BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO DEORE CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-3712BT, 9° backsweep, 12mm rise, 760mm, 35mm
STEM	ONE1 TDS-D622 Alloy, 35mm
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M8100/BR-M8120, hydraulic disc brake
SADDLE	Saddle
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm

WHEELS

TIRES	Schwalbe Nobby Nic Evo Super Ground TL Easy, 29x2.35", ADDIX Speedgrip
WHEELSET	DT Swiss M 1900 Spline DB30; 12x148mm, CENTER LOCK, Tubeless, DT Swiss M 1900 Spline DB30; 15x110mm, CENTER LOCK, Tubeless